

# Uponor

## Aqua Port M-INS

uponor



### Fully insulated body

For installation outside the apartment.

#### Installation/system recommendation

- In floors outside the apartment

#### Application

- Decentralised, instantaneous domestic hot water generation

#### Installation options

- On wall, without cabinet

#### Certificates

- DVGW approval

#### Specifications

- Port fully assembled and pressure tested
- Pipe clamps made of plastic for sound protection and thermal decoupling
- DVGW-certified PM valve with patented triple-sealing technology
- Venting valve
- Thermostatic bypass valve
- Strainer for cold water, 0.5 mm
- Strainer for primary heating supply line, 0.5 mm
- Connection port (marked) for an electrical earthing lug
- Max. operating pressure, heating: PN10
- Max. operating pressure, sanitary: PN10
- Max. operating temperature: 85°C
- Max. differential pressure, heating: 2.5 bar
- Min. pressure, sanitary: 2.0 bar
- Fitting material, sanitary: CW617N
- Fitting material, heating: CW617N, CW614N
- Pipe material: Stainless steel, 1.4401
- Measurements: W/H/D 255 × 376 × 148 mm

# Uponor Aqua Port M-INS

For domestic hot  
water preparation.

## Accessories codes

- 19** Domestic hot water capacity indication (l/min.)
- CB** Copper-brazed stainless steel heat exchanger for domestic hot water preparation
- TL** Thermostatic temperature limiter for domestic hot water, with submersible sensor
- HA** Water hammer arrester on domestic hot water side
- NC** No cold water outlet from heat interface unit
- IB** Fully insulated body

Item no.	Accessories codes					
1121439	19	CB	TL	HA	NC	IB

Further information  
on Uponor Aqua  
Port M-INS



➤ Technical  
information

# uponor

## Uponor Corporation

Ilmalantori 4  
00240 Helsinki  
Finland  
www.uponor.com  
1146092 - 08/2024 - EN

# Moving ➤ Water