

Uponor

Aqua Port M-XS

Uponor



To ensure the best hygiene in the system

With the Aqua Port M-XS near a distant tapping point, the total volume of hot water will be reduced.

Installation/system recommendation

- Addition to HIU for distant tapping point

Application

- Decentralised, instantaneous domestic hot water generation

Installation options

- On wall, without cabinet

Certificates

- DVGW approval

Specifications

- Port fully assembled and pressure tested
- Pipe clamps made of plastic for sound protection and thermal decoupling
- DVGW-certified PM valve with patented triple-sealing technology
- Venting valve
- Thermostatic bypass valve
- Strainer for cold water, 0.5 mm
- Strainer for primary heating supply line, 0.5 mm
- Connection port (marked) for an electrical earthing lug
- Max. operating pressure, heating: PN10
- Max. operating pressure, sanitary: PN10
- Max. operating temperature: 85°C
- Max. differential pressure, heating: 2.5 bar
- Min. pressure, sanitary: 2.0 bar
- Fitting material, sanitary: CW617N
- Fitting material, heating: CW617N, CW614N
- Pipe material: Stainless steel, 1.4401
- Measurements: W/H/D 255 × 376 × 148 mm

Uponor Aqua Port M-XS

For domestic hot
water preparation.

Accessories codes

- 15, 19** Domestic hot water capacity indication (l/min.)
- St** Stainless steel heat exchanger brazed without non-ferrous metal for domestic hot water preparation
- BP** Supply line preheating function
- DI** Primary differential pressure controller at the heat interface unit inlet
- TL** Thermostatic temperature limiter for domestic hot water, with submersible sensor

| Item no. | Accessories codes | | | | |
|----------|-------------------|----|----|----|----|
| 1135567 | 15 | St | BP | DI | TL |
| 1135568 | 19 | St | BP | DI | TL |
| 1135572 | 15 | St | BP | DI | |
| 1135574 | 19 | St | BP | DI | |

Further information
on Uponor Aqua
Port M-XS



➤ Technical
information

uponor

Uponor Corporation

Ilmalantori 4
00240 Helsinki
Finland
www.uponor.com
1146093 - 08/2024 - EN

Moving ➤ Water