

DECLARATION OF PERFORMANCE

CPR-5-IWW-1000008

1. Unique identification code of the product-type:

SEPTIC TANK 4,5M3 WL, product number 1073116
SEPTIC TANK 4,5M3 WL AP12, product number 1073118
SEPTIC TANK 6M3 WL, product number 1073119
SEPTIC TANK 6M3 WL AP12, product number 1073121
SEPTIC TANK 8M3 WL, product number 1073122
SEPTIC TANK 8M3 WL AP12, product number 1073124
SEPTIC TANK 12M3 WL, product number 1074981
SEPTIC TANK 12M3 WL AP12, product number 1073126

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

n/a

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Prefabricated septic tank

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Uponor Infra AB, SE 513 81 Fristad, Sweden

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

*Uponor Infra Oy, FIN-15561 Nastola, Finland
Uponor Infra A/S, DK-4450 Jyderup, Denmark
Uponor Infra AS, N-0195 Oslo, Norway
Uponor Infra AS, 13811 Tallinn, Estonia
Uponor Latvia SIA, LV-1045 Riga, Latvia
Uponor UAB, LT-06115 Vilnius, Lithuania*

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 12566-1:2000/A1:2003

Initial type testing of product under system 3 performed by:

- Danish Technological Institute, Gregersensevej, P.O. Box 141, 2630 Taastrup, Denmark, Notified Body No. 04-002
Test report number: 281284-11/2008*

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

n/a

9. Declared performance

<div>CE</div> <div>08</div>		
Essential characteristics	Performance	Harmonised technical specification
Hydraulic efficiency	0,62 g of beads	EN 12566-1:2000/A1:2003
Nominal capacity	4,5 m ³ 6,0 m ³ 8,0 m ³ 12,0 m ³	
Watertightness	Pass	
Crushing resistance	Pass	
Durability	Pass	
Reaction to fire	NPD	
Release of dangerous substance	NDP	

10. The performance of the product identified in point 1 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Niila Tast
Application Manager
IWW
30.9.2024