

uponor

Uponor Accesso 600

Technical factsheet

Uponor Accesso 600

Uponor Accesso 600 is an inspection chamber for sewer and stormwater networks. The system consists of bottom, riser pipe, sealing ring, top part solution and connectors.

The connections are provided with sealing ring for smooth pipes in dimension 160-400mm. The same bottom can be used with corrugated and ribbed pipes like IQ, Ultra Double, and Ultra Rib 2 using eccentric connectors.

The corrugated riser pipe is cut to required length on site and placed in riser socket with sealing ring in the first groove. IQ 684/600 single wall riser pipe is available in 6 and 3m lengths. Double wall riser pipes can also be used with the system.

The system is suitable for use with standard top solutions; the selection depends on traffic load and surface.

Uponor Accesso 600 can be installed on six meter depth and maximum five meter ground water level.







- ✓ Wide and versatile portfolio
- ✓ Sockets allow 7,5° movement in all directions
- ✓ Flat and stable bottom
- ✓ Excellent flow properties
- ✓ No built-in drop saves the gravity fall across the installation


Application	Sewer and stormwater networks
Material	Polypropylene (PP)
Colour	Black
Pipe dimensions	160, 200, 250, 315, 400mm
Riser pipe connection	600mm
Sealing ring	SBR (can be changed to oil-resistant)
Standards	EN 13596-2, EN 476



Bottom types

PP, inlet and outlet reversible in straight, bend and T-models

		160mm	200mm	250mm	315mm	400mm
	0-180° straight	✓	✓	✓	✓	✓
	0-90° bend	✓	✓	✓	✓	
	0-120° bend	✓	✓	✓	✓	
	0-150° bend	✓	✓	✓	✓	
	T 90° right/left inlet	✓	✓	✓	✓	
	Cross 90° right & left inlet	✓	✓	✓	✓	



D mm	Dn mm	L mm	M mm	H mm	H1 mm	h1 mm
160	689	735	105	393	158	121
200	689	755	125	435	158	142
250	689	785	155	487	158	168
315	689	795	180	556	158	203
400	689	815	215	645	158	246

Connector

Eccentric, PP, for connection with double wall and ribbed pipes



Type	L mm	L1 mm	M mm
200/200S	265	130	135
250/250S	320	160	160
315/315S	405	190	215

Riser pipe and sealing ring

PP, for inspection chamber 600



Type	L=3000 mm	L=6000 mm
Riser pipe 684/600	✓	✓
Sealing ring 600 SBR		
Telescopic sealing ring 600/590		