


| Item number | Separator model | Nominal capacity [l/s] | Sludge sensor height SI [mm] | Oil sensor height OI [mm] | Inner diameter di [mm] | Outside diameter do [mm] | Height h [mm] | In/out diameter DN [mm] | Inlet height h1 (B+30) [mm] | Outlet height h2 (B) [mm] | HS [mm] |
|-------------|-----------------|------------------------|------------------------------|---------------------------|------------------------|--------------------------|---------------|-------------------------|-----------------------------|---------------------------|---------|
| 1141770 | OS-PE-3-0,3 | 3 | 299 | 850 | 800 | 900 | 1608 | 160 | 1040 | 1010 | 108 |
| 1141771 | OS-PE-3-0,66 | 3 | 420 | 1100 | 1000 | 1140 | 1915 | 160 | 1290 | 1260 | 165 |
| 1141772 | OS-PE-6-0,6 | 6 | 382 | 1020 | 1000 | 1140 | 1835 | 160 | 1210 | 1180 | 165 |
| 1141773 | OS-PE-6-1,2 | 6 | 531 | 1320 | 1200 | 1350 | 2165 | 160 | 1510 | 1480 | 195 |
| 1141774 | OS-PE-6-2,5 | 6 | 622 | 1520 | 1600 | 1790 | 2430 | 160 | 1710 | 1680 | 260 |
| 1141775 | OS-PE-10-1 | 10 | 442 | 1150 | 1200 | 1350 | 1995 | 160 | 1340 | 1310 | 195 |
| 1141776 | OS-PE-10-2 | 10 | 650 | 1580 | 1400 | 1580 | 2455 | 160 | 1770 | 1740 | 225 |
| 1141777 | OS-PE-10-3 | 10 | 746 | 1780 | 1600 | 1790 | 2690 | 160 | 1970 | 1940 | 260 |
| 1141778 | OS-PE-20-2 | 20 | 650 | 1680 | 1400 | 1580 | 2635 | 200 | 1910 | 1880 | 225 |
| 1141779 | OS-PE-20-4 | 20 | 637 | 1700 | 2000 | 2250 | 2755 | 200 | 1930 | 1900 | 325 |
| 1141780 | OS-PE-30-3 | 30 | 746 | 2040 | 1600 | 1790 | 3120 | 250 | 2310 | 2280 | 260 |
| 1141781 | OS-PE-30-6 | 30 | 955 | 2490 | 2000 | 2250 | 3635 | 250 | 2760 | 2730 | 325 |
| 1141782 | OS-PE-40-4 | 40 | 637 | 2050 | 2000 | 2250 | 3300 | 315 | 2360 | 2330 | 325 |
| 1141783 | OS-PE-50-5 | 50 | 796 | 2260 | 2000 | 2250 | 3470 | 315 | 2530 | 2500 | 325 |
| 1141784 | OS-PE-60-6,1 | 60 | 971 | 2720 | 2000 | 2250 | 3970 | 315 | 3030 | 3000 | 325 |

Uponor

Description
Mounting dimensions

Drawing number
0000363032



Sheet: 1/1