

## **DECLARATION OF PERFORMANCE**

CPR-5-IWW-1000007

1. Unique identification code of the product-type:

SEPTIC TANK 4,5M3, product number 1136581 SEPTIC TANK 4,5M3 WITH PUMP, product number 1136582

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

n/a

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Prefabricated septic tank

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Uponor Infra AB, SE 513 81 Fristad, Sweden

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Uponor Infra Oy, FIN-15561 Nastola, Finland Uponor Infra A/S. DK-4450 Jyderup, Denmark Uponor Infra AS, N-0195 Oslo, Norway Uponor Infra AS, 13811 Tallinn, Estonia Uponor Latvia SIA, LV-1045 Riga, Latvia Uponor UAB, LT-06115 Vilnius, Lithuania

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 12566-1:2000/A1:2003

Initial type testing of product under system 3 performed by:

- Prüfinstitut für Abwassertechnik (PIA GmbH), Hergenrather Weg 30, 52074 Aachen, Germany, Notified Body No. 1739
  - Test reports: PIA2022-WD-NC-2211-1065, PIA2022-HWG-2211-1065
- Eurofins, Box 47, FI-02151 Espoo, Finland, Notified Body No. 0809
  Test report: EUFI29-22001035-T1



8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

n/a

## 9. Declared performance

Essential characteristics	Performance		Harmonised technical specification
Hydraulic efficiency	Gravity: With pump:	0,4 g of beads 0,7 g of beads	
Nominal capacity	Gravity: With pump:	4,5 m <sup>3</sup> 4,0 m <sup>3</sup>	
Watertightness	Pass		
Crushing resistance	Pass		EN 12566-1:2000/A1:2003
Durability	Pass		
Reaction to fire	NPD		
Release of dangerous substance	NDP		

10. The performance of the product identified in point 1 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Niila Tast

**Application Manager** 

ıww

19.12.2022