



# Chamber riser pipe 400



- Lightweight double wall construction with high ring stiffness and axial pull/push strength.
- Easy to handle and install.
- Excellent sealing stability and leak tightness.
- Gray inside, two outside colors.

## Uponor 400 Chamber riser pipe

Riser pipes are used in sewer and storm water inspection chambers. The assortment includes different lengths, but the riser pipe can always be cut to a specific length.

Application	Sewer and Storm
Material	PP
Dimension	400/350
Length	2m and 6m
Depth	Up to 6m.
Colour	Red-brown and Black with white stripe, gray inside
Standards	-
Approvals	-

# Assortment and features

System properties	Standard
Riser pipe 400 Double Wall, SN $\geq$ 4	
Sealing ring (sold separately)	EN 681-1
Manchette (sold separately)	EN 681-1

Uponor Chamber riser pipes	Uponor no	Local database numbers	EAN-no	Dimension mm	Length mm
CHAMBER RISER PIPE 400 RED BROWN 6M PP DW J	1144164	NRF not yet RSK 2373057	6414900328081	Ø 400/350	6000
CHAMBER RISER PIPE 400 RED BROWN 2M PP DW J	1144165	NRF not yet RSK 2373058	6414900328098	Ø 400/350	2000
CHAMBER RISER PIPE 400 BLACK 6M PP DW J	1144166	NRF not yet RSK 2373059	6414900328104	Ø 400/350	6000
CHAMBER RISER PIPE 400 BLACK 2M PP DW J	1144272	NRF not yet RSK 2373061	6414900328463	Ø 400/350	2000
Sealing ring (sold separately)	1143907	Not yet	6414900326940	Ø 401/338	22
Manchette (sold separately)	1120878	NRF 3220683 RSK not yet	6414900370196	Ø 419/401	69

# Moving > Water

**uponor**

**Uponor Corporation**

Ilmalantori 4

00240 Helsinki

Finland

**T** +358 (0)20 129 211

**F** + 358 (0)20 129 2841

[www.uponor.com](http://www.uponor.com)