

Technical datasheet

Uponor Tripla™ cable ducting pipes



- Made in PE.
- Installed in both normal and difficult conditions.
- Easy connection with both smooth and corrugated pipes.
- Have EPD.

Tripla

Uponor Tripla™ is Uponor's third generation of cable protection pipes and the completely unique pipe design makes it possible to use the pipe for normal installations but also for installations where extra high ring stiffness is required. The pipe has a welded-on sleeve with an oil- and chemical-resistant sealing ring and is completely waterproof.

Technical data

Specifications	
Application	Cable protection system
Material	Polyethylene (PE)
Colour	Yellow, Green, Orange, Red
Dimensions	110, 140 and 160 mm
Length	6 m
Design	Three-layer pipe with smooth inside and outside
Class	SRN according to EBR KJ41:21 Kabelförläggning, max 145kV SN8 or SN16 according to ISO 9969
Standards	Manufactured according to the requirements of EN 50626-1 and testing requirements of SS 424 14 37 7 Kabelförläggning i mark, ed 6. Tightness according to the requirements in EN 13476.

Properties

System properties		Standard
Ring stiffness	SN8 SN16	ISO 9969
Impact strength	Normal design Pointed tip Fall weight 10 kg, height 500mm	SS 424 14 37 7 ed 6

Assortment


The assortment for Uponor Tripla available at

<https://www.uponor.com/fi-fi/tuoteluettelo-infra/kaapelinsuojaus/kaapelinsuojaputket/tripla-putket>

Excellence in Flow

Lisätietoa järjestelmistämme:

www.uponor.com



Tässä esitetyt tiedot ja tekniset tiedot (jäljempänä "tiedot") eivät ole sitovia, ellei niitä ole nimenomaisesti vahvistettu kirjallisesti. Tiedot eivät muodosta mitään ilmaista, oletettua tai taattua ominaisuuksia, taattuja ominaisuuksia tai taattua kestävyyttä. Kaikkia tietoja voidaan muuttaa. Sovelletaan Georg Fischer Piping Systemsin yleisiä myyntiehtoja.

