



Premium telescopic covers



- Adjustable height
- Low maintenance and renovation costs
- Secure locking feature of cover protects against accidents with children
- PU seal ensures cover tightness

Telescopic covers

For inspection, stormwater, and drainage chambers.




Ductile iron cover. Telescope pipe dimension 160. PU seal.




Class D400 (40 ton).

Application	Storm, sewage, or drainage chambers
Material	PP
Dimension	160, 315 (L-63 and L-65 Premium) 600 (U600/560 Premium)
Length	700, 885 or 2000 (L-63 and L-65 Premium) 865 (U600/560 Premium)
Colour	Red brown (L-63 and L-65 Premium) Black (U600/560 Premium)
Standards	SS-EN 124
Approvals	-

Properties and assortment

System properties	Standard
Adjustable height	SS-EN 124
Secure locking feature	

L-63 Premium	Uponor no	Local no	Dimension mm	Length mm
	1071745	2348837 (RSK) 3220487 (NRF)	160	700
	1091701	6585217 (RSK)	160	2000
	1050632	2348688 (RSK) 3220046 (NRF)	200/160	70

L-65 Premium	Uponor no	Local no	Dimension mm	Length mm
	1071744	2348836 (RSK)	315	885
	1091702	6585216 (RSK)	315	2000
	1050633	2357045 (RSK) 3220059 (NRF)	400/315	

U600/560 Premium	Uponor no	Local no	Dimension mm	Length mm
	1143136	6585286 (RSK)	600/560	865

Moving > Water

uponor

Uponor Corporation

Ilmalantori 4

00240 Helsinki

Finland

T +358 (0)20 129 211

F + 358 (0)20 129 2841

www.uponor.com